



DAC11AU

Digital to Analogue Converter (DAC)



Description

Our DAC11AU is designed to convert either Coaxial or Optical signals from a digital signal to analogue stereo audio. This provides the perfect cost-effective solution when connecting the digital audio output from a TV display to an analogue input on an amplifier. The DAC11AU utilises 192kHz sample rates for enhanced sound reproduction.

Key Features

- DAC (Digital to Analogue Audio Converter) converts either digital optical or coaxial to analogue stereo left / right audio output *
- Auto-detects digital connection in use
- Optical digital input has priority over coaxial digital input
- Supports sample rates 32kHz, 44.1kHz, 48kHz, 96kHz & 192kHz up to 24-bit resolution
- Plug-and-play solution

** DAC11AU does not down-mix Dolby / dts / multi-channel audio signals*

Specifications

- Audio Input Connectors: 1 x Optical (S/PDIF) & 1 x RCA (S/PDIF)
- Audio Output Connectors: 2 x Analogue stereo left / right (RCA)
- Product Dimensions (W x D x H): 45 x 65 x 25mm (with connections)
- Product Dimensions (W x D x H): 45 x 55 x 25mm (without connections)
- Product Weight: 0.1kg (excluding accessories)
- Carton / Box Dimensions (W x D x H): 95 x 135 x 55mm
- Shipping Weight: 0.3kg
- Operating Temperature: 32°F to 104°F (0°C to 40°C)
- Storage Temperature: -4°F to 140°F (-20°C to 60°C)
- Power Supply: 5V/1A DC, barrel type connection
- Mounting kit included

Box Contents

- 1 x DAC11AU
- 1 x 5V/1A DC power supply
- 1 x Mounting kit
- 1 x User manual