


DVX D15 Active 15"/1.4" two-way multifunctional speaker cabinet



A two-way system featuring 15"/1.4" speakers, the DVX D15 is the enclosure of choice for use as a fullrange FOH speaker or a powerful drum monitor. It delivers punchy, assertive bass response without requiring an added subwoofer. Its integrated, high-performance **digipro**[®] digital power amp delivers very high sound pressure levels, exceedingly dynamic response, and tight, clean low-end response. Loaded with high-quality speakers sporting neodymium magnets to reduce weight, it provides premium audio performance with maximum reliability and minimum power compression.

A 1.4" driver with a 2,5" voice coil designed to handle highest loads renders vocals with a powerful, assertive punch, easily throwing signals across medium-to-longer distances.

The housing's multifunctional design incorporates rigging points and a slanted panel serving monitoring purposes. The onboard controller even provides a special monitor setup that specifically adapts the enclosure's performance for use as a monitor. It also serves as a controller for an active equalizer, x-over, limiter, and phase and delay time alignment. The DVX D15 is the perfect match for DVA Series subwoofers.



DVX D15 Technical data

► Audio data

Frequency response	49 Hz - 20 kHz (-10 dB)
Frequency response	57 Hz - 19 kHz (+3 dB)
Max SPL:	132 dB
Bass/midrange woofer:	15" RCF neodymium 3,5" voice coil
High frequency driver:	1.4" RCF neodymium compression driver, 2,5" titanium voice coil
Horn:	60° x 40° aluminum CD horn
Rotatable:	Yes

► Amp and processor

Power supply:	1000-watt switched-mode power supply with PFC
HF amp:	Class-D 250 W/RMS
Bass amp:	Class-D 500 W/RMS
Cooling:	Convection, fan-free
System presets:	FOH, Monitor
Limiter:	RMS, thermal limiters
X-over frequency:	1320 Hz, 24 dB/octave

► Input section

Signal input:	XLR fem. balanced
Signal link:	XLR male balanced
Input sensitivity:	Max. -3dBu
Mains:	PowerCon Input and Link

► Hardware

Enclosure:	Multiplex coated with textured black lacquer
Handles:	Two aluminium side grips, one on top
Pole mount:	36 mm
Angles up:	45° for monitoring applications
Grille:	1,5mm Metal backed with acoustic foam rubber
Rigging points:	6x rails, 6 x M10 and 4x 10mm quick-release
Dimensions (W x H x D):	430 x 690 x 450 mm 16.9" x 27.2" x 17.7"
Weight:	25 kg, 55 lbs
Optional accessories:	Mounting yoke, Gig bag