

# RS 85

## Headphones | Wireless Hi-fi Headphones

RS 85-4 (434 MHz) Cat. No. 004956 RS 85-8 (863 MHz) Cat. No. 004957 RS 85-9 (925 MHz) Cat. No. 004959

#### **General Description**

The RS 85 wireless RF headphone system with open, circumaural headphones features HiDyn *plus*™ noise reduction for wide dynamics and superb sound quality, ensuring a very natural and detailed sound reproduction. The RS 85 comes equipped with Center-Lock Auto-Tuning. A simple touch of a button, and the headphones will automatically adjust to the transmitter (and can simply be re-tuned with a second touch if it locks on to your neighbour's transmitter).



### **Features**

- Uncompromising sound quality due to HiDyn *plus*™ noise reduction
- Lightweight, comfortable headphones incorporate volume control, one-touch auto-tuning and SAW input filter to eliminate RF interference
- Reception through walls and ceilings, in the home and outside in the garden within a range of up to approx. 100 m (30 m for 925 MHz variant)
- Three switchable channels (2 for 863 MHz variant)
- Supplied with second accupack
- Special audio filter in the transmitter eliminates TV interference

### Recommended Accessories

 SCART adaptor (Scart plug to Scart plug + 3.5 mm jack coupling)
 HDR 85-4 supplementary headphones (434 MHz)

■ HDR 85-4 supplementary headphones (434 MHz) Cat. No. 004966
■ HDR 85-8 supplementary headphones (863 MHz) Cat. No. 004967

■ HDR 85-9 supplementary headphones (925 MHz)

Cat. No. 004968

Cat. No. 077798

### **Replacement Parts**

Ear pads (1 pair)

Cat. No. 077965

### **Product Variants**

RS 85-8 UK:

863 MHz variant with UK plug-in mains unit

Cat. No. 004958

### Technical Data – HDR 85 Headphone Receiver

dynamic, open
20–22,000 Hz
< 0.5 %
101 dB
via BA 151 accupack, 2.4 V
over 4 hrs per accupack
approx. 160 g

weight (with BA 151)approx. 160 g
Technical Data – T 85 Transmitter Carrier frequencies
434 MHz variant: 434.15 MHz, 433.4 MHz,
434.5 MHz (switchable)
836 MHz variant:863.25 MHz, 863.75 MHz (switchable)
925 MHz variant:925.0 MHz, 926.0 MHz,
926.5 MHz (switchable)
Rangeup to approx. 100 m
(up to approx. 30 m for 925 MHz variant)
ModulationFM stereo
Signal-to-noise ratiotyp. > 85 dBA
Audio connector3.5 mm stereo jack plug with
adaptor to 1/4" (6.3 mm) stereo jack plug and
adaptor to RCA phono connectors
Charging options 2, for headphones plus second BA 151
Weight (w/o mains unit)approx. 186 g
Dimensions