



# Tourguide 2020-D

## SK 2020-D



The SK 2020-D, a digital Tourguide transmitter, will allow you to deliver a highly professional guided tour. Combining the bodypack transmitter with an headworn or clip-on microphone, will give you total freedom of movement during your tour. You will have both hands free to describe an object, make a presentation and express your point.

The transmitter can be easily and comfortably operated, and is highly robust. The backlit display confirms channel choice, the radio signal and the status of the battery. Two jacks for the microphone and line ensure variable utilization. For example, you will be able to transmit an external audio source such as music from a portable CD player via your transmitter and continue to talk or mute the microphone.

### ACCESSORIES

EZL 2020-20 L	Charging case	Art. no. 500542
L 2015	Quick-charging unit	Art. no. 009828

### FEATURES

- Digital RF signal transmission
- 6 channels in the licence-free
- frequency range
- Microphone input (3.5 mm screw-type jack socket) with adjustable sensitivity
- Line input (3.5 mm screw-type jack socket) with adjustable sensitivity
- Audio level meter for microphone and line input
- Backlit display for status informations

### DELIVERY INCLUDES

- SK 2020-D
- BA 2015
- Quick Guide

### SPECIFICATIONS

Modulation	2 FSK (46K0F1D)
Frequency range	863 – 865 MHz
Frequency range (US)	926 – 928 MHz
Channels	6
RF output power	10 mW
RF output power (US)	max. 50 mV/m (distance: 3 m)
AF frequency response	100 – 7,000 Hz
Max. input voltage at mic/ line input	
microphone:	650 mV <sub>eff</sub> (sensitivity –36 dB)
line:	2 V <sub>eff</sub> (sensitivity –24 dB)
Operating time	typ. 8 h
Power supply	BA 2015 accupack, 2.4 V or 2 AA size batteries, 1.5 V
Temperature range	0 – 50 °C
Dimensions	approx. 82 x 64 x 24 mm
Weight	approx. 160 g (incl. BA 2015 accupack)

### PRODUCT VARIANTS

SK 2020-D-US	Art. no. 500549
SK 2020-D	Art. no. 500548



# Tourguide 2020-D

## SK 2020-D

### DIMENSIONS

